


# BT-MAS 403

## HEAT SHRINK TOOLHOLDERS



'B' FORM ALSO AVAILABLE

Taper	Ordering No.	Stock	d	L	D1	D2	L3
40	BT40-TT60-090G63	●	6	90	20	27	36
	BT40-TT80-090G63	●	8	90	20	27	36
	BT40-TT10-090G63	●	10	90	24	32	42
	BT40-TT12-090G63	●	12	90	24	32	47
	BT40-TT14-090G63	●	14	90	27	34	47
	BT40-TT16-090G63	●	16	90	27	34	50
	BT40-TT18-090G63	●	18	90	33	42	50
	BT40-TT20-090G63	●	20	90	33	42	52
BT40-TT25-100G63	●	25	100	44	53	58	
40	BT40-TT06-120G63	●	6	120	20	27	36
	BT40-TT08-120G63	●	8	120	20	27	36
	BT40-TT10-120G63	●	10	120	24	32	42
	BT40-TT12-120G63	●	12	120	24	32	47
	BT40-TT14-120G63	●	14	120	27	34	47
	BT40-TT16-120G63	●	16	120	27	34	50
	BT40-TT18-120G63	●	18	120	33	42	50
	BT40-TT20-120G63	●	20	120	33	42	52
BT40-TT25-120G63	●	25	120	44	53	58	
40	BT40-TT06-160G63	●	6	160	20	32	36
	BT40-TT08-160G63	●	8	160	20	32	36
	BT40-TT10-160G63	●	10	160	24	34	42
	BT40-TT12-160G63	●	12	160	24	34	47
	BT40-TT14-160G63	●	14	160	27	42	47
	BT40-TT16-160G63	●	16	160	27	42	50
	BT40-TT18-160G63	●	18	160	33	50	50
	BT40-TT20-160G63	●	20	160	33	50	52
BT40-TT25-160G63	●	25	160	44	53	58	
50	BT50-TT06-100G63	●	6	100	20	27	36
	BT50-TT08-100G63	●	8	100	20	27	36
	BT50-TT10-100G63	●	10	100	24	32	42
	BT50-TT12-100G63	●	12	100	24	32	47
	BT50-TT14-100G63	●	14	100	27	34	47
	BT50-TT16-100G63	●	16	100	27	34	50
	BT50-TT18-100G63	●	18	100	33	42	50
	BT50-TT20-100G63	●	20	100	33	42	52
	BT50-TT25-110G63	●	25	110	44	53	58
	BT50-TT32-110G63	●	32	110	44	53	58
50	BT50-TT06-120G63	○	6	120	20	27	36
	BT50-TT08-120G63	○	8	120	20	27	36
	BT50-TT10-120G63	○	10	120	24	32	42
	BT50-TT12-120G63	○	12	120	24	32	47
	BT50-TT14-120G63	○	14	120	27	34	47
	BT50-TT16-120G63	○	16	120	27	34	50
	BT50-TT18-120G63	○	18	120	33	42	50
	BT50-TT20-120G63	○	20	120	33	42	52
	BT50-TT25-120G63	○	25	120	44	53	58
BT50-TT32-120G63	○	32	120	44	53	58	
50	BT50-TT06-160G63	○	6	160	20	32	36
	BT50-TT08-160G63	○	8	160	20	32	36
	BT50-TT10-160G63	○	10	160	24	34	42
	BT50-TT12-160G63	○	12	160	24	34	47
	BT50-TT14-160G63	○	14	160	27	42	47
	BT50-TT16-160G63	○	16	160	27	42	50
	BT50-TT18-160G63	○	18	160	33	50	50
	BT50-TT20-160G63	○	20	160	33	50	52
BT50-TT25-160G63	○	25	160	44	60	58	
BT50-TT32-160G63	○	32	160	44	60	58	

For Shank Tolerance h6  
Balanced G6.3@15,000 rpm  
Max run out at nose 0.003mm

● = Standard Product - Normally Ex-Stock  
○ = Standard Product - Availability on Request

Packing Unit and Ordering Example  
1 piece BT50-TT20-160G63