


HEAT SHRINK TOOLHOLDERS



Taper	Ordering No.	Stock	d	L	D1	D2	L3
40 FORM 'A'	DV40-TT03-080G63	○	3*	80	15	20	20
	DV40-TT04-080G63	○	4*	80	15	20	20
	DV40-TT05-080G63	○	5*	80	15	20	25
	DV40-TT06-080G63	●	6	80	20	27	36
	DV40-TT08-080G63	●	8	80	20	27	36
	DV40-TT10-080G63	●	10	80	24	32	42
	DV40-TT12-080G63	●	12	80	24	32	47
	DV40-TT14-080G63	●	14	80	27	34	47
	DV40-TT16-080G63	●	16	80	27	34	50
	DV40-TT18-080G63	●	18	80	33	42	50
DV40-TT20-080G63	●	20	80	33	42	52	
DV40-TT25-100G63	●	25	100	44	53	58	
40 FORM 'A'	DV40-TT06-120G63	○	6	120	20	27	36
	DV40-TT08-120G63	○	8	120	20	27	36
	DV40-TT10-120G63	○	10	120	24	32	42
	DV40-TT12-120G63	○	12	120	24	32	47
	DV40-TT14-120G63	○	14	120	27	34	47
	DV40-TT16-120G63	○	16	120	27	34	50
	DV40-TT18-120G63	○	18	120	33	42	50
DV40-TT20-120G63	○	20	120	33	42	52	
DV40-TT25-120G63	○	25	120	44	53	58	
40 FORM 'A'	DV40-TT06-160G63	●	6	160	20	32	36
	DV40-TT08-160G63	●	8	160	20	32	36
	DV40-TT10-160G63	●	10	160	24	34	42
	DV40-TT12-160G63	●	12	160	24	34	47
	DV40-TT14-160G63	●	14	160	27	42	47
	DV40-TT16-160G63	●	16	160	27	42	50
	DV40-TT18-160G63	●	18	160	33	42	50
DV40-TT20-160G63	●	20	160	33	42	52	
DV40-TT25-160G63	○	25	160	44	53	58	
40 FORM 'B'	DV40B-TT06-080G63	●	6	80	20	27	36
	DV40B-TT08-080G63	●	8	80	20	27	36
	DV40B-TT10-080G63	●	10	80	24	32	42
	DV40B-TT12-080G63	●	12	80	24	32	47
	DV40B-TT14-080G63	●	14	80	27	34	47
	DV40B-TT16-080G63	●	16	80	27	34	50
	DV40B-TT18-080G63	●	18	80	33	42	50
DV40B-TT20-080G63	●	20	80	33	42	52	
DV40B-TT25-100G63	●	25	100	44	53	58	
40 FORM 'B'	DV40B-TT06-120G63	○	6	120	20	27	36
	DV40B-TT08-120G63	○	8	120	20	27	36
	DV40B-TT10-120G63	○	10	120	24	32	42
	DV40B-TT12-120G63	○	12	120	24	32	47
	DV40B-TT14-120G63	○	14	120	27	34	47
	DV40B-TT16-120G63	○	16	120	27	34	50
	DV40B-TT18-120G63	○	18	120	33	42	50
DV40B-TT20-120G63	○	20	120	33	42	52	
DV40B-TT25-120G63	○	25	120	44	53	58	
40 FORM 'B'	DV40B-TT06-160G63	○	6	160	20	32	36
	DV40B-TT08-160G63	○	8	160	20	32	36
	DV40B-TT10-160G63	○	10	160	24	34	42
	DV40B-TT12-160G63	○	12	160	24	34	47
	DV40B-TT14-160G63	○	14	160	27	42	47
	DV40B-TT16-160G63	○	16	160	27	42	50
	DV40B-TT18-160G63	○	18	160	33	42	50
DV40B-TT20-160G63	○	20	160	33	42	52	
DV40B-TT25-160G63	○	25	160	44	53	58	

For Shank Tolerance h6
 * Shank Tolerance h4 or better
 Balanced G6.3@15,000 rpm
 Max run out at nose 0.003mm

● = Standard Product - Normally Ex-Stock
 ○ = Standard Product - Availability on Request

Packing Unit and Ordering Example
 1 piece DV40B-TT20-160G63