


HEAT SHRINK EXTENSIONS

HEAT SHRINK EXTENSIONS									
	Shank	Ordering No.	Stock	d	L	D1	D2	L3	Type
 TYPE 1	12mm	SS120-TT03-060	●	3*	60	9	12	20	1
		SS120-TT04-060	●	4*	60	9	12	20	1
		SS120-TT05-060	●	5*	60	9	12	25	1
		SS120-TT06-060	●	6	60	15	19	36	2
	16mm	SS120-TT08-060	●	8	60	15	19	36	2
		SS160-TT03-060	●	3*	60	9	15	20	1
		SS160-TT04-060	●	4*	60	9	15	20	1
		SS160-TT05-060	●	5*	60	9	15	25	1
TYPE 2 Run Out 0.003mm at the nose	20mm	SS160-TT06-060	●	6	60	15	20	36	2
		SS160-TT08-060	●	8	60	15	20	36	2
		SS200-TT03-060	●	3*	60	9	15	20	1
		SS200-TT04-060	●	4*	60	9	15	20	1
		SS200-TT05-060	●	5*	60	9	15	25	1
		SS200-TT06-060	●	6	60	15	19.5	36	1
	25mm	SS200-TT08-060	●	8	60	15	19.5	36	1
		SS200-TT10-060	●	10	60	20	27	42	2
		SS200-TT12-060	●	12	60	20	27	47	2
		SS250-TT14-060	○	14	60	24	32	47	2
		SS250-TT16-060	○	16	60	24	32	50	2

Suitable for through coolant

* For 3,4,5mm Dia. Shank Tolerance h4 or better

For 6mm - 16mm Dia. Shank Tolerance h6

● = Standard Product - Normally Ex-Stock
 ○ = Standard Product - Availability on Request

Packing Unit and Ordering Example
 1 piece SS250-TT16-060